

This listing of claims will replace all prior versions, and listings, of claims in the application. Please amend claims 1 and 4 and cancel claims 2 and 6 as follows:

Listing of Claims:

1. (Currently amended) A differential apparatus for transmitting torque from an output shaft of a driving source to two axle shafts while producing a rotational difference between the two axle shafts, the differential apparatus comprising:

a differential case coaxially and integrally joined with the output shaft, wherein the output shaft and the differential case form a single and monolithic cast member.

2. (Canceled)

3. (Original) The differential apparatus according to claim 1, wherein the driving source is a motor.

4. (Currently amended) A differential apparatus, arranged between two axle shafts, for rotating the two axle shafts at different speeds or at the same speed, the differential apparatus comprising:

differential gears for connecting the two axle shafts to each other;
an output shaft member having a differential case portion for accommodating the differential gears and an output shaft portion integrally formed with the differential case portion from the same material, wherein the output shaft member is a single and monolithic cast member; and

a driving source that supplies the output shaft member with torque.

5. (Original) The differential apparatus according to claim 4, wherein the driving source is a motor, the differential apparatus further comprising:

a motor case for accommodating the motor; and
two bearings that support the output shaft member in a manner rotatable with
respect to the motor case, one of the bearings being arranged on one end of the output shaft
portion and the other one of the bearings being arranged on one end of the gear case portion
opposite to the output shaft portion.

6. (Canceled)

7. (Original) The differential apparatus according to claim 4, wherein the
output shaft member is made of cast iron.

8. (Original) The differential apparatus according to claim 4, wherein the
two axle shafts are linked to two drive wheels of an industrial vehicle, respectively.